Wire Basket Tray No-Splice Supports

- Hubbell No-Splice Supports provide labor and time saving installation
- No-Splice Supports provide a dual function of supporting and splicing the wire basket tray
- Reduces the number of splice kits required for tray installation
- Basket tray mounting hardware supplied with each No-Splice Support

Hubbell offers a line of No-Splice Supports that provide a dual function, tray splicing and support. Utilizing the ends of the tray's bottom rails, the basket tray mechanically "locks" into the supports and are secured with a supplied ¼"-20 self tapping screws and washer supports which maintains the tray's equipment ground classification. These time savings products can contribute to a reduction in job man hours.

A wide range of threaded rod (all thread) can be used with the supports. The center supports having a 0.56" opening and the center supports with (2) 0.51" openings, which can meet most job specifications. Hubbell offers No-Splice Supports in electro-zinc plated or black powder painted finishes.

FEATURES

- Available pre-galvanized or black powder coat paint finishes.
- Supports compatible with standard round wire basket tray or flat shaped basket tray
- For each tray size, supports maintain the same UL Listed/ cUL Certified as equipment ground conductor as standard splice kits
- Requires supports every 5 feet

SPECIFICATIONS

- UL Listed
- cUL Certified

No-Splice Center Support

No-Splice Ceiling Support

Wire Basket Tray No-Splice Supports

No-Splice Supports reduces the number of splice kits required for tray installations.

Factory ends of bottom rails lock into the No-Splice Support notches.

1. Insert end of rails of first tray into notches of No-Splice Support.

2. Lower and lock tray into support.

3. Insert end of rails of second tray into notches of No-Splice Support.

4. Lower and lock tray into support.

5. Secure basket tray to support with supplied hardware.

No-Splice Support*

Tray Width	Center Support			Ceiling Support		
	Qty. per Box	Pre-Galvanized	Black Powder Coat	Qty. per Box	Pre-Galvanized	Black Powder Coat
6" (152)	1	**HBTNSCTRS6**	**HBTNSCTRS6BK**	-	–	–
8" (203)	1	**HBTNSCTRS8**	**HBTNSCTRS8BK**	-	–	–
12" (305)	1	**HBTNSCTRS12**	**HBTNSCTRS12BK**	1	**HBTNSCLGS12**	**HBTNSCLGS12BK**
16" (406)	1	**HBTNSCTRS16**	**HBTNSCTRS16BK**	1	**HBTNSCLGS16**	**HBTNSCLGS16BK**
18" (457)	1	**HBTNSCTRS18**	**HBTNSCTRS18BK**	1	**HBTNSCLGS18**	**HBTNSCLGS18BK**
20" (508)	1	**HBTNSCTRS20**	**HBTNSCTRS20BK**	1	**HBTNSCLGS20**	**HBTNSCLGS20BK**
24" (610)	1	**HBTNSCTRS24**	**HBTNSCTRS24BK**	1	**HBTNSCLGS24**	**HBTNSCLGS24BK**

*Note: *Install every 5 feet. Splice hardware included.*

Center Support

Ceiling Support

No-Splice Time Savings Chart

Tray Width	Splice Qty	Traditional Splice	No-Splice Support	Time Savings (%)
2x12	4	1 Minute 15 seconds	10 Seconds	86%
4x12	6	2 Minutes 15 seconds	10 Seconds	93%
4x18	7	2 Minutes	20 Seconds	87%
4x24	8	3 Minutes	20 Seconds	89%

Printed in U.S.A. Specifications subject to change without notice.